DEVICE SPECIFICATIONS

NI PXI-5661

2.7 GHz RF Vector Signal Analyzer with Digital Downconversion

This document lists specifications for the NI PXI-5661 RF vector signal analyzer.

Specifications are warranted under the following conditions:

- 20 minutes warm-up time
- Calibration cycle maintained
- Chassis fan speed set to High
- NI-RFSA instrument driver used
- NI-RFSA instrument driver self-calibration performed after instrument temperature is stable.

Specifications describe the warranted, traceable product performance over ambient temperature ranges of 0 °C to 55 °C, unless otherwise noted.

Typical values describe useful product performance beyond specifications that are not covered by warranty and do not include guardbands for measurement uncertainty or drift. Typical values may not be verified on all units shipped from the factory. Unless otherwise noted, typical values cover the expected performance of units over ambient temperature ranges of 15 °C to 35 °C with a 90% confidence level, based on measurements taken during development or production.

Specifications are subject to change without notice. For the most recent NI 5661 specifications, visit *ni.com/manuals*.

To access NI 5661 documentation, navigate to Start»All Programs»National Instruments» NI-RFSA»Documentation.



Hot Surface If the NI 5661 has been in use, it may exceed safe handling temperatures and cause burns. Allow the NI 5661 to cool before removing it from the chassis.

Contents

Ports	2
Frequency Characteristics	2
Internal Frequency Reference	
Spectral Purity	
Spurious Responses	



Amplitude Specifications	8
	8
	9
	9
	nly)9
	erter Only)
Modulation Specifications	
	lation Error Ratio (MER)
RF Input Characteristics	
IF/Baseband	
Front Panel I/O	14
NI 5600 RF Downconverter Module	14
NI 5142 IF Digitizer Module	
Power Requirements	
Calibration	
Physical Characteristics	
Environment	
Operating Environment	17
_	17
	17
<u> </u>	17
Compliance and Certifications	
Environmental Management	
D .	
Ports	
RF	1
IF output	1
Frequency Characteristic	cs

Frequency range	9 kHz to 2.7 GHz
Instantaneous bandwidth	20 MHz
Resolution bandwidth	Fully adjustable (<1 Hz to 10 MHz)

Table 1. Selectivity

Window	60 dB : 3 dB Ratio
Flat Top	2.5, maximum
7-term Blackman-Harris	4.1, maximum

Table 2. Hardware Tuning Resolution

Hardware Module	Resolution	
	Internal Sample Clock Timebase External Sample Clock Timebase	
NI 5142 digitizer	355 nHz ¹ Sample Clock timebase/2 ⁴⁸	
NI 5600 downconverter	1 MHz, minimum	

Table 3. NI 5600 Downconverter Tuning Speed (15 °C to 35 °C)

Accuracy	Settling Time
1% of step size	10 ms, maximum
0.01% of step size	20 ms, maximum
0.0001% of step size	30 ms, maximum

Digitizer tuning speed 1 ms

Internal Frequency Reference

Frequency	10 MHz
Temperature stability	±20 ppb, maximum (referenced to 25 °C)
Aging	
Per year	±100 ppb, maximum
Per day	±1 ppb after 72 hours
Initial achievable accuracy	±50 ppb, maximum
Locking range	±0.5 ppm, minimum
Lock time for the NI 5600 (to external reference)	10 s, maximum

¹ With 100 MHz Sample Clock.

Spectral Purity

Table 4. Maximum Phase Noise

Offset Frequency	Noise Density
1 kHz	-80 dBc/Hz
10 kHz	-90 dBc/Hz
30 kHz	-95 dBc/Hz
100 kHz	-110 dBc/Hz
1 MHz	-120 dBc/Hz



Note 1 GHz carrier; instantaneous bandwidth \leq 10 MHz.

Figure 1. Typical Phase Noise at 1 GHz (Instantaneous Bandwidth ≤ 10 MHz)





Figure 2. Typical Phase Noise at 1 GHz (Instantaneous Bandwidth >10 MHz)



Residual FM (Continuous wave, 300 Hz to 3 kHz integration bandwidth)

10 Hz_{pk-pk} in 10 ms, maximum

Spurious Responses

Table 5. Sideband Spurs

Offset Frequency	Level
≥10 kHz	-70 dBc, maximum
<10 kHz	-55 dBc, maximum



Note -30 dBm input signal; 0 dB attenuation; -30 dBm reference level.

Table 6. Second-Order Harmonic Distortion (Input IP₂)

Input Signal	Distortion ^{2, 3}	Mixer Input IP ₂ ⁴
<120 MHz	-77 dBc, typical	42 dBm, typical
120 MHz to <400 MHz	-78 dBc, maximum	42 dBm, minimum
	-81 dBc. typical	45 dBm, typical
400 MHz to <800 MHz	-70 dBc, maximum	34 dBm, minimum
	-75 dBc, typical	39 dBm, typical
800 MHz to <1.1 GHz	-74 dBc, maximum	38 dBm, minimum
	-80 dBc, typical	44 dBm, typical
1.1 GHz to <1.25 GHz	-70 dBc, maximum	34 dBm, minimum
	-74 dBc, typical	38 dBm, typical
1.25 GHz to 1.35 GHz	-65 dBc, maximum	28 dBm, minimum
	-71 dBc, typical	35 dBm, typical
>1.35 GHz ⁵	_	_

Table 7. Third-Order Intermodulation Distortion (Input IP₃)

Input Signal	Distortion	Mixer Input IP ₃
10 MHz to <1 GHz	-80 dBc, maximum	10 dBm, minimum
1 GHz to <2 GHz	-84 dBc, maximum	12 dBm, minimum
2 GHz to 2.7 GHz	-86 dBc, maximum	13 dBm, minimum



Note Two -30 dBm input tones, ≥200 kHz apart; -30 dBm reference level; mixer level -30 dBm.

Measurements performed with a single CW tone, -26 dBm at the RF input. Reference level set to -20 dBm and mixer level set to -30 dBm (RF attenuation = 10 dB).

³ Above 35 °C, add an additional amplitude variation of 1 dB to the maximum *Distortion* levels.

⁴ Calculated from *Distortion* levels.

Frequencies above 1.35 GHz produce a second harmonic distortion outside the specified tuning frequency range of the device.

Table 8. Input-Related Spurs

Frequency	Level
≥5 MHz	-70 dBc, maximum
<5 MHz	-60 dBc, maximum



Note -30 dBm input signal; 0 dB attenuation; -30 dBm reference level.

Table 9. Residual Spurs

Frequency	Level	
≥20 MHz	-100 dBm, maximum	
<20 MHz	-70 dBm, maximum	



Note Input terminated; no input signal; 0 dB attenuation; -30 dBm reference level.


Table 10. Noise Density

Frequency	Averaged Noise Level	
20 MHz to <1 GHz	-135 dBm/Hz, maximum	
1 GHz to <2 GHz	-134 dBm/Hz, maximum	
2 GHz to <2.5 GHz	-130 dBm/Hz, maximum	
2.5 GHz to 2.7 GHz	-129 dBm/Hz, maximum	



Note Input terminated; no input signal; 0 dB attenuation; -30 dBm reference level.

Figure 3. Typical Noise Density⁶



Amplitude Specifications

Input Levels

Amplitude range

< Averaged Noise Level to +30 dBm

Table 11. Maximum Safe Continuous RF Power

RF Attenuation	Level	
Enabled (≥10 dB)	+30 dBm	
Disabled (0 dB)	+20 dBm	

RF input attenuation

0 dB to 50 dB in 10 dB steps

⁶ Input terminated; no input signal; 0 dB attenuation; -30 dBm reference level.

Accuracy

Table 12. Relative Accuracy

Frequency	Accuracy		
25 MHz to 2 GHz	±0.75 dB		
	±0.5 dB, typical		
>2 GHz	±1.25 dB		
	±0.9 dB, typical		
Note Wid			



Note With respect to 100 MHz; 15 °C to 35 °C, with calibration correction.

Table 13. Absolute Accuracy

Frequency	Accuracy	
25 MHz to 2 GHz	±1 dB	
	±0.6 dB, typical	
>2 GHz	±1.5 dB	
	±1 dB, typical	



Note 15 °C to 35 °C, with calibration correction.

Group Delay Variation

20 MHz bandwidth

30 ns_{pk-pk} (15 °C to 35 °C)

Linearity (NI PXI-5600 Downconverter Only)⁷

Table 14. Mixer 1 dB Gain Compression Point

Frequency	1 dB Compression Point	
10 MHz to 1 GHz	0 dBm, minimum	
1 GHz to 2 GHz	2 dBm, minimum	

Table 14. Mixer 1 dB Gain Compression Point (Continued)

Frequency	1 dB Compression Point
2 GHz to 2.7 GHz	4 dBm, minimum



Note At RF input port, 0 dB RF attenuation.

Dynamic Range (NI PXI-5600 Downconverter Only)8

Table 15. Compression (1 dB) to Noise Dynamic Range (DR)

Frequency	Compression-Noise DR	
10 MHz to 1 GHz	135 dB, minimum	
1 GHz to 2 GHz	136 dB, minimum	
2 GHz to 2.7 GHz	134 dB, minimum	



Note Resolution bandwidth = 1 Hz; 0 dB RF attenuation.

Table 16. Maximum Intermodulation Distortion (SFDR) Dynamic Range (DR)

Frequency	Intermodulation DR	
10 MHz to 1 GHz	96 dB, minimum	
1 GHz to 2 GHz	97 dB, minimum	
2 GHz to 2.7 GHz	95 dB, minimum	



Note $2/3 \times (IP_3 - Averaged Noise Level)$; resolution bandwidth = 1 Hz; mixer level = -30 dBm.

Table 17. Second Harmonic⁹

Frequency	Second Harmonic	
<120 MHz	88 dB	
120 MHz to 400 MHz	88 dB	
400 MHz to 800 MHz	84 dB	

⁷ For NI PXI-5600 downconverter only, digitizer may clip under certain conditions.


⁸ For NI PXI-5600 downconverter only, digitizer may clip under certain conditions.

 $^{^9}$ 1/2 × (IP₂ - Averaged Noise Level); resolution bandwidth = 1 Hz; mixer level = -36 dBm.

Table 17. Second Harmonic⁹ (Continued)

Frequency	Second Harmonic
800 MHz to 1.1 GHz	86 dB
1.1 GHz to 1.25 GHz	84 dB
1.25 GHz to 1.35 GHz	81 dB
>1.35 GHz	_

Figure 4. Typical Dynamic Range (1 Hz Resolution Bandwidth at 1 GHz)



 $^{^9}$ 1/2 × (IP₂ - *Averaged Noise Level*); resolution bandwidth = 1 Hz; mixer level = -36 dBm.

Modulation Specifications

Error Vector Magnitude (EVM) and Modulation Error Ratio (MER)

Table 18. 800 MHz Carrier Frequency (Typical)

QAM Order	Symbol Rate (kHz)	System Equalization Enabled ¹⁰		System Equalization Disabled	
		EVM (% rms)	MER (dB)	EVM (% rms)	MER (dB)
M = 4	270	_	_	1.1	39
	1,220	1.0	40	1.9	35
	3,840	1.4	37	2.3	32
	5,360	1.6	36	2.5	32
M = 16	270	_	_	0.8	39
	1,220	1.0	40	1.4	34
	3,840	0.9	39	1.8	32
	5,360	1.1	39	1.9	32
M = 64	270	_	_	0.7	39
	1,220	0.6	41	1.3	35
	3,840	0.7	40	1.6	32
	5,360	0.8	39	1.7	32



Note Root-raised-cosine filter; alpha = 0.25; 2,000 symbols.

System equalization applied using NI Modulation Toolkit software version 3.0, which removes linear distortion effects from modulation quality measurements. This data includes linear distortions from the signal source, the channel, and the receiver.

Table 19 1 900 MHz Carrier Frequency

QAM Order	Symbol Rate (kHz)	System Equalization Enabled ¹¹		System Equalization Disabled	
		EVM (% rms)	MER (dB)	EVM (% rms)	MER (dB)
M = 4	270	_	_	1.2	38
	1,220	1.0	40	1.9	34
	3,840	1.4	37	2.4	32
	5,360	1.6	36	2.6	32
M = 16	270	_	_	0.9	39
	1,220	0.8	40	1.5	34
	3,840	0.8	40	1.8	32
	5,360	0.9	39	1.9	32
	10,000	1.0	38	2.4	30
M = 64	270	_	_	0.9	38
	1,220	0.7	40	1.4	34
	3,840	0.7	40	1.6	32
	5,360	0.8	39	1.7	32
	10,000	0.8	37	2.2	30



Note Root-raised-cosine filter; alpha = 0.25; 2,000 symbols.

RF Input Characteristics

Nominal impedance	50 Ω
Input coupling	AC
Maximum DC input voltage	±25 VDC ¹²

¹¹ System equalization applied using NI Modulation Toolkit software version 3.0, which removes linear distortion effects from modulation quality measurements. This data includes linear distortions from the signal source, the channel, and the receiver.

 $^{^{12}}$ DC levels up to ± 25 VDC at input will not damage the NI 5661. However, high transient currents from low-impedance DC step voltages at input can cause damage.

Voltage Standing Wave Ratio (VSWR)

Table 20. NI 5661 VSWR

Attenuation	Frequency	VSWR
Enabled (10 dB to 50 dB) ¹³	9 kHz to 2.2 GHz	1.3:1 maximum
	2.2 GHz to 2.7 GHz	1.5:1 maximum
Disabled (0 dB)	9 kHz to 2.2 GHz	1.6:1 maximum
	2.2 GHz to 2.7 GHz	2.5:1 maximum

LO emission from RF input <-87 dBm, maximum

IF/Baseband

Resolution	14 bits
System IF frequency range	5 MHz to 25 MHz
Sample rate	100 MS/s
Digital downconverter (OSP) bandwidth	20 MHz to 4.88 kHz using 100 MS Sample Clock timebase
Onboard memory	64 MB, 256 MB



Note Refer to the *NI PXI/PCI-5142 Specifications* document for additional IF/baseband and onboard signal processing (OSP) specifications.

Front Panel I/O

NI 5600 RF Downconverter Module

SMA female	
50 Ω	
AC	
SMA female	
50 Ω	
	50 Ω AC SMA female

¹³ Available in 10 dB steps.

riec	quency	5 MHz to 25 MHz
Am	plitude	0 dBm full scale
FREQ R	EF IN	
Con	nector	SMA female
Imp	edance	50 Ω
Inpu	ut amplitude	-5 dBm to +15 dBm
Max	ximum safe input level	+16 dBm
Max	kimum DC input voltage	±5 V
Inpu	nt frequency range	$10 \text{ MHz} \pm 0.5 \text{ ppm}$
10 MHz	OUT (2 ports)	
Con	nector	SMA female
Imp	edance	50 Ω
Sign	nal	Square wave
Am	plitude	$\pm0.5~V$ (+7 dBm) into 50 Ω (± 1 V into oper circuit)
Acc	uracy	Refer to the <i>Internal Frequency Reference</i> section
PXI 10 N	MHz I/O	
Con	nector	SMA female
Imp	edance	50 Ω
Inpu	ut amplitude	-5 dBm to +15 dBm
	put amplitude	0.5 V (+7 dBm) into 50 Ω

CH0, CH1	
Connector	BNC female
Impedance	50 Ω
Maximum input overload 7 V _{rms}	with $ Peaks \le 10 \text{ V}(30 \text{ dBm})$
CLK IN	
Connector	SMB female
Impedance	50 Ω
Input amplitude	-10 dBm to +13 dBm (Square Wave)

Maximum input overload 7 V_{rms} with $|Peaks| \le 10 \text{ V}(30 \text{ dBm})$

CLK OUT	
Connector	SMB
Output impedance	50 Ω
Logic type	3.3 V CMOS
Maximum driver current	$\pm 48 \text{ mA}$
PFI 0, PFI 1	
Connector	9-pin mini-circular DIN
Logic type	3.3 V CMOS
Maximum input voltage	5.5 V

Power Requirements

Table 21. NI 5661 Power Requirements (Voltages ±5%)

Module	+3.3 VDC	+5 VDC	+12 VDC	-12 VDC
NI 5600 RF downconverter	920 mA	2.3 A	700 mA	115 mA
NI 5142 IF digitizer	1 A	1.7 A	800 mA	270 mA

Calibration

Interval		
NI 5600	1 year	
NI 5142	2 years	

Physical Characteristics

NI 5600	3U, Three Slot, PXI/cPCI module,
	$21.6 \text{ cm} \times 6.0 \text{ cm} \times 13.0 \text{ cm}$
	$(8.5 \text{ in.} \times 2.4 \text{ in.} \times 5.1 \text{ in.})$
NI 5142	3U, One Slot, PXI/cPCI module,
	$21.6 \text{ cm} \times 2.0 \text{ cm} \times 13.0 \text{ cm}$
	$(8.5 \text{ in.} \times 0.8 \text{ in.} \times 5.1 \text{ in.})$
ght (combined unit)	1,165 g (41.1 oz)

Environment

Input to earth

Maximum altitude	2,000 m (at 25 °C ambient temperature)
Pollution Degree	2
Indoor use only.	
Operating Environment	
Ambient temperature range	0 °C to 50 °C (Tested in accordance with IEC 60068-2-1 and IEC 60068-2-2. Meets MIL-PRF-28800F Class 3 low temperature limit and MIL-PRF-28800F Class 2 high temperature limit.)
Relative humidity range	10% to 90%, noncondensing (Tested in accordance with IEC 60068-2-56.)
Storage Environment	
Ambient temperature range	-40 °C to 70 °C (Tested in accordance with IEC 60068-2-1 and IEC 60068-2-2. Meets MIL-PRF-28800F Class 3 limits.)
Relative humidity range	5% to 95%, noncondensing (Tested in accordance with IEC 60068-2-56.)
Shock and Vibration	
Operating shock	30 g peak, half-sine, 11 ms pulse (Tested in accordance with IEC 60068-2-27. Meets MIL-PRF-28800F Class 2 limits.)
Random vibration	
Operating	5 Hz to 500 Hz, 0.3 g_{rms}
Nonoperating	5 Hz to 500 Hz, 2.4 g _{rms} (Tested in accordance with IEC 60068-2-64. Nonoperating test profile exceeds the requirements of MIL-PRF-28800F, Class 3.)

0 VDC, Installation Category I

Compliance and Certifications

Safety

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA 61010-1



Note For UL and other safety certifications, refer to the product label or the *Online* Product Certification section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- AS/NZS CISPR 11: Group 1, Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



Note In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.



Note Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



Note For EMC declarations, certifications, and additional information, refer to the Online Product Certification section.

CE Compliance (E

This product meets the essential requirements of applicable European Directives, as follows:

- 2006/95/EC; Low-Voltage Directive (safety)
- 2004/108/EC; Electromagnetic Compatibility Directive (EMC)

Online Product Certification

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for this product, visit ni.com/

certification, search by model number or product line, and click the appropriate link in the Certification column.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the Minimize Our Environmental Impact web page at *ni.com/environment*. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document

Waste Electrical and Electronic Equipment (WEEE)

EU Customers At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

电子信息产品污染控制管理办法(中国 RoHS)

😝 🐠 中国客户 National Instruments 符合中国电子信息产品中限制使用某些有害物 质指令(RoHS)。关于 National Instruments 中国 RoHS 合规性信息,请登录 ni.com/environment/rohs china。 (For information about China RoHS compliance, go to ni.com/environment/rohs china.)

Refer to the *NI Trademarks and Logo Guidelines* at ni.com/trademarks for information on NI trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering NI products/technology, refer to the appropriate location: **Help»Patents** in your software, the patents_txt file on your media, or the *National Instruments Patent Notice* at ni.com/patents. You can find information about end-user license agreements (EULAs) and third-party legal notices in the readme file for your NI product. Refer to the *Export Compliance Information* at ni.com/legal/export-compliance for the NI global trade compliance policy and how to obtain relevant HTS codes, ECCNs, and other import/export data. NI MAKES NO EXPRESS OR IMPLIED WARRANTIES AS TO THE ACCURACY OF THE INFORMATION CONTAINED HEREIN AND SHALL NOT BE LIABLE FOR ANY ERRORS. U.S. Government Customers: The data contained in this manual was developed at private expense and is subject to the applicable limited rights and restricted data rights as set forth in FAR 52.227-14, DFAR 252.227-7014, and DFAR 252.227-7015.